

## Selection table for refurbishment outlets

| Type       | For connection<br>to piping<br>of diameter | Type of existing downpipe [DN] |    |     |     |     |     |     |    |    |    |     |     |     |     |    |     |     |     |     |     |     |     |     |
|------------|--------------------------------------------|--------------------------------|----|-----|-----|-----|-----|-----|----|----|----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|
|            |                                            | Cast iron                      |    |     |     |     |     |     |    | PE |    |     |     | PVC |     |    |     | PP  |     |     |     |     |     |     |
|            |                                            | 70                             | 80 | 100 | 110 | 125 | 150 | 200 | 63 | 75 | 90 | 110 | 125 | 150 | 200 | 70 | 100 | 125 | 150 | 200 | 100 | 125 | 150 | 200 |
| TW SAN 50  | 54-72 mm                                   | x                              |    |     |     |     |     |     | x  | x  |    |     |     |     |     |    | x   |     |     |     |     |     |     |     |
| TW SAN 63  | 69-81 mm                                   | x                              | x  |     |     |     |     |     |    | x  | x  |     |     |     |     |    | x   |     |     |     |     |     |     |     |
| TW SAN 75  | 79-102 mm                                  |                                | x  |     |     |     |     |     |    | x  |    |     |     |     |     |    |     |     |     |     |     |     | x   |     |
| TW SAN 90  | 99-106 mm                                  |                                |    | x   |     |     |     |     |    |    | x  |     |     |     |     |    | x   |     |     |     |     |     | x   |     |
| TW SAN 100 | 106-116 mm                                 |                                |    |     | x   |     |     |     |    |    |    |     |     |     |     |    |     |     |     |     |     |     |     |     |
| TW SAN 110 | 116-129 mm                                 |                                |    |     |     | x   |     |     |    |    | x  |     |     |     |     |    | x   |     |     |     |     |     | x   |     |
| TW SAN 125 | 144-154 mm                                 |                                |    |     |     |     | x   |     |    |    |    | x   |     |     |     |    |     | x   |     |     |     |     | x   |     |
| TW SAN 140 | 154-186 mm                                 |                                |    |     |     |     | x   |     |    |    |    |     | x   |     |     |    |     | x   | x   |     |     |     | x   | x   |
| TW SAN 160 | 186-200 mm                                 |                                |    |     |     |     |     | x   |    |    |    |     |     | x   |     |    |     |     |     | x   |     |     |     | x   |